


“Which Proc Should I Learn First?” A STAT Instructor’s Top 5 Modeling Procedures

Catherine Truxillo, Ph.D.
Manager, Analytical Education
SAS



The Target Audience for this Talk



sas THE POWER TO KNOW.

A Common Question

“Can you tell me when to use
each of the procedures
in SAS/STAT?”

3

sas THE POWER TO KNOW.

SAS/STAT Has A Lot of Procedures

<input type="checkbox"/> The ACECLUS Procedure	<input type="checkbox"/> The KRIGE2D Procedure	<input type="checkbox"/> The PRINCOMP Procedure
<input type="checkbox"/> The ADAPTIVEREG Procedure	<input type="checkbox"/> The LATTICE Procedure	<input type="checkbox"/> The PRINQUAL Procedure
<input type="checkbox"/> The ANOVA Procedure	<input type="checkbox"/> The LIFEREG Procedure	<input type="checkbox"/> The PROBIT Procedure
<input type="checkbox"/> The BOXPLOT Procedure	<input type="checkbox"/> The LIFETEST Procedure	<input type="checkbox"/> The QUANTLIFE Procedure
<input type="checkbox"/> The CALIS Procedure	<input type="checkbox"/> The LOESS Procedure	<input type="checkbox"/> The QUANTREG Procedure
<input type="checkbox"/> The CANCORR Procedure	<input type="checkbox"/> The LOGISTIC Procedure	<input type="checkbox"/> The QUANTSELECT Procedure
<input type="checkbox"/> The CANDISC Procedure	<input type="checkbox"/> The MCMC Procedure	<input type="checkbox"/> The REG Procedure
<input type="checkbox"/> The CATMOD Procedure	<input type="checkbox"/> The MOS Procedure	<input type="checkbox"/> The ROBUSTREG Procedure
<input type="checkbox"/> The CLUSTER Procedure	<input type="checkbox"/> The MI Procedure	<input type="checkbox"/> The RSREG Procedure
<input type="checkbox"/> The CORRRESP Procedure	<input type="checkbox"/> The MIANALYZE Procedure	<input type="checkbox"/> The SCORE Procedure
<input type="checkbox"/> The DISCRIM Procedure	<input type="checkbox"/> The MIXED Procedure	<input type="checkbox"/> The SEQDESIGN Procedure
<input type="checkbox"/> The DISTANCE Procedure	<input type="checkbox"/> The MODECLUS Procedure	<input type="checkbox"/> The SEQTEST Procedure
<input type="checkbox"/> The FACTOR Procedure	<input type="checkbox"/> The MULTTEST Procedure	<input type="checkbox"/> The SIM2D Procedure
<input type="checkbox"/> The FASTCLUS Procedure	<input type="checkbox"/> The NESTED Procedure	<input type="checkbox"/> The SIMNORMAL Procedure
<input type="checkbox"/> The FMM Procedure	<input type="checkbox"/> The NLIN Procedure	<input type="checkbox"/> The STDIZE Procedure
<input type="checkbox"/> The FREQ Procedure	<input type="checkbox"/> The NLMMED Procedure	<input type="checkbox"/> The STDRATE Procedure
<input type="checkbox"/> The GAM Procedure	<input type="checkbox"/> The NPARTWAY Procedure	<input type="checkbox"/> The STEFOSC Procedure
<input type="checkbox"/> The GENMOD Procedure	<input type="checkbox"/> The ORTHOREG Procedure	<input type="checkbox"/> The SURVEYFREQ Procedure
<input type="checkbox"/> The GLMMIX Procedure	<input type="checkbox"/> The PHREG Procedure	<input type="checkbox"/> The SURVEYLOGISTIC Procedure
<input type="checkbox"/> The GLM Procedure	<input type="checkbox"/> The PLAN Procedure	<input type="checkbox"/> The SURVEYMEANS Procedure
<input type="checkbox"/> The GLMMOD Procedure	<input type="checkbox"/> The PLM Procedure	<input type="checkbox"/> The SURVEYPHREG Procedure
<input type="checkbox"/> The GLMPower Procedure	<input type="checkbox"/> The PLS Procedure	<input type="checkbox"/> The SURVEYSELECT Procedure
<input type="checkbox"/> The GLMSELECT Procedure	<input type="checkbox"/> The POWER Procedure	<input type="checkbox"/> The TPSPLINE Procedure
<input type="checkbox"/> The HPMIXED Procedure		<input type="checkbox"/> The TRANSREG Procedure
<input type="checkbox"/> The INBREED Procedure		<input type="checkbox"/> The TREE Procedure
<input type="checkbox"/> The KDE Procedure		<input type="checkbox"/> The TTEST Procedure
		<input type="checkbox"/> The VARCLUS Procedure
		<input type="checkbox"/> The VARCOMP Procedure
		<input type="checkbox"/> The VARIOGRAM Procedure

4

Focus on Modeling Procedures

Focusing just on “supervised” statistical modeling procedures, we can rule out many statistical procedures such as ACECLUS, FASTCLUS, PRINCOMP, FACTOR, CORRESP, SURVEYSELECT, STDIZE, MDS, MI, ... the list goes on.

That still leaves somewhere in the neighborhood of 40 procedures.

What about the modeling procedures that statisticians love to use?

5

Everyone Has Their Favorite Procedures

Mike's Favorites:

LOGISTIC
PHREG
GLM
REG
MIXED

Cat's Favorites:

GLIMMIX
CALIS
DISCRIM
MIXED
GLMSELECT

Marc's Favorites:

PHREG
LOGISTIC
MIXED
GENMOD
GLMSELECT


Chris's Favorites:

GLIMMIX
MIXED
SURVEYREG
SURVEYLOGISTIC
REG

Danny's Favorites:

MCMC
GLIMMIX
REG
GLM
LIFEREG

6



Everyone Has Their Favorite Procedures

Mike's Favorites:

- LOGISTIC
- PHREG
- GLM
- REG
- MIXED

Marc's Favorites:

- PHREG
- LOGISTIC
- MIXED
- GENMOD
- GLMSELECT

Cat's Favorites:

- GLIMMIX
- CALIS
- DISCRIM
- MIXED
- GLMSELECT

Chris's Favorites:


- GLIMMIX
- MIXED
- SURVEYREG
- SURVEYLOGISTIC
- REG

Danny's Favorites:

- MCMC
- GLIMMIX
- REG
- GLM
- LIFEREG

This is not a beauty contest!

7



What is Best to Learn First?

Assuming you already know your way around statistical models, the best procedures to learn first should:

1. fit the models you most commonly need
2. have a lot of useful functionality
3. be relatively easy to use

Let's consider each of these criteria:

8

What is Best to Learn First?

Assuming you already know your way around statistical models, the best procedures to learn first should:

1. fit the models you most commonly need

This requires knowing your subject-matter and what your colleagues commonly use.

- Ask around!
- Look at old SAS programs in your company.
- See whether there are newer procedures that handle the same models more efficiently.

9

What is Best to Learn First?

Assuming you already know your way around statistical models, the best procedures to learn first should:

2. have a lot of useful functionality

You want to get a lot for your learning effort.

- No uni-taskers!
- Options for many of the different variations of the type of analysis a procedure is designed for.
- Great graphics!

10

What is Best to Learn First?

Assuming you already know your way around statistical models, the best procedures to learn first should:

3. be relatively easy to use

You want to be working right away.

- Defaults should be the most commonly preferred options
- Syntax should be consistent with most statistical literature for the type of model
- Syntax should be streamlined and easy to learn

11

Four Procedures That Fit the Bill (plus one you will also want to know)

1. PROC GLMSELECT
2. PROC LOGISTIC
3. PROC GLIMMIX
4. PROC PHREG
5. and a bonus: PROC PLM

12

The GLMSELECT Procedure

- Have you heard of REG and GLM?
- These procedures are used to fit linear models (ANOVA, ANCOVA, regression).
- GLM has syntax for modeling categorical predictors and comparing groups
 - reducing model effects requires iterative programming
- REG has several model selection methods and diagnostics for regression modeling.
 - categorical variables require creating dummy variables and extra syntax to keep them together in model selection.

13

The GLMSELECT Procedure

Combines the most commonly used features of GLM and REG, with several new features not currently in REG or GLM. Highlights:

- Many options for how CLASS variables are handled and coded
- PARTITION statement enables holdout assessment for model selection.
- Additional model selection methods (LARS and LASSO)
- Model averaging based on resampling input data
- SCORE statement to perform scoring of holdout or score data sets
- Easy syntax!

14

The GLMSELECT Procedure

General form of the GLMSELECT procedure

```
PROC GLMSELECT data = mydata</options>;  
  <CLASS class-var<options>  
    ...class-var<options>/<generaloptions>;>  
  MODEL y = xeffects<s></options>;  
  <other statements>  
RUN;
```

15

The GLMSELECT Procedure

Example

```
PROC GLMSELECT DATA=sashelp.cars PLOTS=all;  
  CLASS Origin(PARAM=REF REF='Europe' SPLIT)  
    Cylinders(PARAM=ORDINAL);  
  MODEL msrp=Origin Cylinders MPG_City Weight  
    MPG Highway Wheelbase Length  
    /SELECTION=FORWARD;  
RUN;
```

16

The GLMSELECT Procedure

When to use PROC GLMSELECT:

- a linear model: the dependent variable is continuous and approximately normally distributed (conditioned on the predictors)
- there are no random effects
- there are no repeated measures
- the response variable is not censored
- time to an event is not of interest

What if this isn't my scenario??

17

The GLMSELECT Procedure

When to use PROC GLMSELECT:

- **a linear model: the dependent variable is continuous and approximately normally distributed (conditioned on the predictors)**
- there are no random effects
- there are no repeated measures
- the response variable is not censored
- time to an event is not of interest

What if my dependent variable is binary?

18

The LOGISTIC Procedure

The LOGISTIC procedure is the go-to SAS procedure for modeling binary and other categorical response variables.

Highlights:

- Can model binary, ordinal, or nominal responses
- The ODDSRATIO statement can be used for estimating complex effects of interval and categorical predictors, including those involved in interactions and polynomial effects.
- Automated model selection options aid in model building.

19

...

The LOGISTIC Procedure

- Many options for how CLASS variables are coded
- Effective graphics output, including effect plots on either the probability or logit scale, odds ratio plots, and Receiver Operating Characteristic (ROC) curves
- STRATA statement to perform Conditional Logistic Regression on case-control data
- SCORE statement to perform scoring of holdout or score data sets
- Easy syntax!

20

...

The LOGISTIC Procedure

General form of the LOGISTIC procedure

```
PROC LOGISTIC data = mydata</options>;  
  <CLASS class-var<options>  
    ...class-var<options>/<generaloptions>;>  
  MODEL y<options> (or) events/trials =  
    x-effect<s> </options>;  
  <other statements>  
RUN;
```

21

The LOGISTIC Procedure

Example

```
PROC LOGISTIC DATA=trial PLOTS=all;  
  CLASS trt gender Y;  
  MODEL y(EVENT='Yes')= trt|age|dose;  
  STRATA gender;  
RUN;
```

22

The LOGISTIC Procedure

When to use PROC LOGISTIC:

- a logistic regression model: the dependent variable is binary, binomial, or multinomial
- there are no random effects
- there are no repeated measures
- the response variable is not censored
- time to an event is not of interest

What if this isn't my scenario??

23

The LOGISTIC Procedure

When to use PROC LOGISTIC:

- **a logistic regression model: the dependent variable is binary, binomial, or multinomial**
- **there are no random effects**
- **there are no repeated measures**
- the response variable is not censored
- time to an event is not of interest

What if I have another distribution?

What if I have random effects or repeated measures?

24

The GLIMMIX Procedure

A procedure for fitting generalized linear mixed models.

Highlights:

- Model responses from any distribution in the exponential family (including normal, binary, and much more!)
- Model multilevel, multiple membership, cross-level, and other types of models with random effects
- Model repeated measures with many covariance structures
- Easy syntax!

25

The GLIMMIX Procedure

General form of the GLIMMIX procedure

```
PROC GLIMMIX data = mydata</options>;  
  <CLASS class-vars;>  
  MODEL y<options> (or) events/trials =  
    x-effect<s> </ DIST= LINK= options>;  
  <RANDOM z-effects /options>;  
  <other statements>  
RUN;
```

26

The GLIMMIX Procedure

Example

```
PROC GLIMMIX DATA=gas METHOD=quad;  
  CLASS state;  
  MODEL spend = affluence /  
    DIST=beta LINK=logit;  
  RANDOM intercept / SUBJECT=state;  
RUN;
```

27

The GLIMMIX Procedure

When to use PROC GLIMMIX:

- a generalized linear model: the dependent variable is normal, binary, multinomial, Poisson, negative binomial, beta, gamma, geometric, or any other distribution in the exponential family.
- there are random effects (or not!)
- there are repeated measures (or not!)
- the response variable is not censored
- time to an event is not of interest

What if this isn't my scenario??

28

The GLIMMIX Procedure

When to use PROC GLIMMIX:

- a generalized linear model: the dependent variable is normal, binary, multinomial, Poisson, negative binomial, beta, gamma, geometric, or any other distribution in the exponential family.
- there are random effects (or not!)
- there are repeated measures (or not!)
- **the response variable is not censored**
- **time to an event is not of interest**

What if my response variable is censored??

What if time to an event is of interest??

29

The PHREG Procedure

A procedure for fitting semi-parametric survival regression models. Highlights:

- many options for how CLASS variables are coded
- an ASSESS statement for assessing the proportional hazards assumption and functional form of a predictor
- STRATA statement to perform a stratified Cox model when the proportional hazards assumption is violated
- programming statements for creating time-dependent predictor variables
- accepts counting process data input, enabling analysis of repeated events and making it even easier to model time dependent predictors
- easy syntax!

30

The PHREG Procedure

General form of the PHREG procedure

```
PROC PHREG data = mydata</options>;
  <CLASS class-var<options>
    ...class-var<options>/<generaloptions>;>
  MODEL time <*censor(list)>
    = x-effect<s> </options>;
or
  MODEL (time1,time2) <*censor(list)>
    = x-effect<s> </options>;
  <other statements>;
RUN;
```

31

The PHREG Procedure

Example

```
PROC PHREG DATA=methadone;
  MODEL time*status(0)=
    dose prison Clin_Int1 Clin_Int2;
  Clin_Int1=Clinic*(time lt 366);
  Clin_Int2=Clinic*(366 le time);
  LABEL
    Clin_Int1=
      "Clinic 2 vs 1 Effect, 1st year"
    Clin_Int2=
      "Clinic 2 vs 1 Effect, 2nd year or later";
RUN;
```

32

The PHREG Procedure

When to use PROC PHREG:

- When time to an event is of interest and your dependent time variable is censored (some events have not been observed at the last observation time)
- When the hazard function (instantaneous event rate) is assumed to be proportional across all values of the independent variables (i.e. the effects of independent variables do not change across time)
- When the effects of predictors on the hazard are of interest, but the shape of the hazard function is not.

33

Bonus: The PLM Procedure



34

Shared Architecture

New architectural changes mean that many procedures have added additional post-fitting capabilities. Statements common to many procedures include:

- CONTRAST
- CODE
- EFFECTPLOT
- ESTIMATE
- LSMEANS
- LSMESTIMATE
- SLICE
- TEST

These features are used at the time of model-fitting.

35

PLM Procedure

The PLM procedure takes model information stored from number of SAS/STAT linear modeling procedures and performs additional inference and scoring **without refitting the original model**.

- Saves time; don't need to rerun your models
- Enables you to meet confidentiality governance

36

STORE Statement

In SAS 9.3 and newer, the following procedures are equipped with the STORE statement, which saves model information as a SAS item store:

GENMOD	PHREG
GLIMMIX	PROBIT
GLM	REG
GLMSELECT	RELIABILITY
LIFEREG	SURVEYLOGISTIC
LOGISTIC	SURVEYPHREG
MIXED	SURVEYREG
ORTHOREG	

37

PLM Procedure

The PLM procedure restores the model fit information and performs post-fitting tasks such as:

- Testing hypotheses
- Computing confidence intervals
- Producing prediction plots
- Scoring a new data set

38

sas THE POWER TO KNOW.	
Post-fitting Statements in PROC PLM	
Statement	Functionality
EFFECTPLOT	Visualizes complex fitted model
ESTIMATE	Estimates and tests custom linear functions of form $L\beta$
LSMEANS	Computes and compares LS-means of fixed effects
LSMESTIMATE	Estimates and tests custom linear functions of LS-means
SCORE	Computes predicted values for a SAS data set
SLICE	Performs partitioned LS-means analysis for higher-order effects of classification variables
TEST	Performs Type I, II, and III F tests for model effects

39

sas THE POWER TO KNOW.	
The PLM Procedure	
When to use PROC PLM:	
<ul style="list-style-type: none"> • When model-fitting is very slow and post-fitting analyses need to be obtained on-demand • When data governance is an issue, as is the case with personal data: <ul style="list-style-type: none"> – Customer data – Student data – Employee data 	
<p>Use of an item store enables safe collaboration on analyses.</p>	

40

Summary

SAS has a diverse and comprehensive library of procedures for your data analysis!

- Use the ones that are best for what you need to do.
- Common syntax makes it easy to learn new procedures after you get started with the first a few.
- For modeling, it can be helpful to familiarize yourself with the procedures described in this talk first, and learn more as you need them.
- PROC PLM performs post-fitting analyses using results from many SAS/STAT modeling procedures.

41

Acknowledgements

Special thanks to Marc Huber for his contributions to this paper.

Special thanks to Lee Bennett and Chip Wells for their review of this paper.

42